PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:		(11) International Publication Number:	WO 00/57089
F16J 15/08	A1	(43) International Publication Date: 28 Ser	otember 2000 (28.09.00)

(21) International Application Number: PCT/US00/07692

(22) International Filing Date: 21 March 2000 (21.03.00)

(30) Priority Data:

60/125,493 22 March 1999 (22,03.99) US

(71) Applicant (for all designated States except US): THE AD-VANCED PRODUCTS COMPANY [US/US]; 33 Defco Park Road, P.O. Box 296, North Haven, CT 06473 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MORE, Dominick, G. [US/US]; 43 Horseshoe Lane, Middletown, CT 06457 (US), STONE, Stephen, S. [US/US]; 100 State Street, Apt. #20, North Haven, CT 06473 (US).

(74) Agents: SLATE, William, B. et al.; Wiggin & Dana, One Century Tower, New Haven, CT 06508-1832 (US). (81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, Fl, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MN, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TI, TM, TI, TI, TZ, UA, UG, US, UZ, VY, UZ, AZ, W, Euruslan patent (AM, AZ, BY, KG, KZ, MD, RU, TI, TM), European patent, GP, GP, CH, CY, DE, DK, ES, Fl, FR, GB, GR, IE, TI, LU, MC, NL, PT, SB, OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TO).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: VACUUM SEAL

(57) Abstract

WWW

An annular metallic vacuum seal (26): 120) having a nested inner (2c): 122) and outer (24: 124) e-sectioned members. The inner member (22: 122) provides longitudinal compressive strength and elasticity and the outer member (24: 124) has a pair of oppositely—directed ridges (40A, 40B) for sealing with a pair of flanges.

